

VESSEL PRINCIPAL PARTICULARS

SHIP'S NAME:	"RIPLEY PRIDE"	FLAG:	INDIA
CALL SIGN :	VTUN	PORT OF REG.:	CHENNAI
L.O.A.:	225.0 M	IMO NO.:	9253832
L.P.P.:	215.0 M	OFFICIAL NO:	4903
BREATH MOULDED:	32.26 M	MMSI:	419001811
DEPTH MOULDED:	19.39 M	SUEZ CANAL ID:	
TPC (SUMMER)	66.8 MT/cm	PANAMA CANAL:	60903
AIR DRAFT	46.83 M	ex Names:	"Koulitsa"/"Emerald Stream"
LIGHT SHIP	10322.6 MT	FWA:	326 mm

TYPE OF VESSEL:	BULK CARRIER
BUILD:	16/03/2003(delivered)
BUILD BY:	OSHIMA SHIBUILDING CO LTD, JAPAN
OWNERS:	Ripley Shipping India IFSC Private Ltd, No 01, Wing C, GIFT Aspire 3, Road 1D, Zone 1 GIFT SEZ, GIFT City Gandhinagar 382355.Gujarat INDIA
MANAGERS:	SuNav Ship Management Private Limited, No 6/13 North Avenue, Kesavaperumalpuram R.A. Puram Chennai, Tamil Nadu 600028, India IMO NO: 6110073
OPERATORS:	Panbulk Shipping DMCC, Unit no - 16.2, JBC 5, Cluster - W, Jumeirah Lake Towers, Dubai, UAE - 28773

SEASONAL MARK	FREEBOARD	DISPL.	DEADWEIGHT	DRAFTS
TFW	4.690	89,093	78,777	14.746
FW	4.980	87,173	76,857	14.452
T	5.016	89,139	78,823	14.420
S	5.310	87,174	76,858	14.126
W	5.604	85,212	74,896	13.832

	Register	Panama Canal	Suez Canal
GROSS TONNAGE:	39966		41548.4
NET TONNAGE:	25503	33041.65	38315.68

CARGO HOLDS				
HOLD	GRAIN CAPACITY(M3)	GRAIN CAPACITY(FT3)	BALE CAPACITY(M3)	TANKTOP LOAD(T/M2)
Nº 1	12,475	440,551.19	12,377	27.7
Nº 2	13,533	477,914.17	13,245	18.5
Nº 3	13,321	470,427.45	13,035	28.9
Nº 4	12,571	443,941.41	12,302	18.5
Nº 5	13,320	470,392.13	13,035	28.9
Nº 6	13,315	470,215.56	13,030	18.5
Nº 7	11,940	421,657.81	11,847	29.2
Total	90,475	3,195,099.73	88,871	

MAIN ENGINE: B&W 5S60 MC-C
AUX. ENGINES: 3 x DAIHATSU DIESEL 5DK-20
MAX.CONT.OUTPUT: 8789 kW/86 RPM
V.L.S.F.O.CAP: 2192.1 CU.M (100%)
L.S.M.O.CAP: 433.4 CU.M (100%)
F.W.CAP: 500 CU.M
CAP:Sludges+ Bilge 66,00 m3

DIST. FROM BOW TO BRIDGE: 193.75 m
DIST. FROM BRIDGE TO AFT : 31.25 m
 DISTANCE FROM BOW / CH.1 : 20 M
 DIST. FWD H1 TO AFT H7 : 170 M
 KEEL TO H/COVER NO1 23.m NO2-7 22.2 m
 Propeller dia 6.70 m

CLASS SOCIETY: L R S & I R S
 CLASS NOTATIONS : | 100A1 Bulk Carrier, Strengthened for Heavy Cargo, Hold Nos. 2, 4 and 6 May Be Empty, ESP, ESN, LI, LMC UMS
P&I:Steamship Mutual Underwriting Association Limited

LIGHT BALLAST: 22453 M3 / 23017 MT
HEAVY BALLAST: 35024 M3/35902 MT
BWTS: ERMA FIRST FIT 1200 BWTS

INMARSAT C TLX: 463734426
MMSI 636021303

ANCHOR LENGTH: 12 Shackles P & S
TUG BOLLARD PULL SWL 88.3 T

RIPLEY PRIDE

MASTER